

(19) World Intellectual Property  
Organization  
International Bureau



540,918  
Rec'd PCT/PTO 29 JUN 2005




(43) International Publication Date  
15 July 2004 (15.07.2004)

PCT

(10) International Publication Number  
WO 2004/058458 A1

- (51) International Patent Classification<sup>7</sup>: B25J 9/00 (74) Agent: CELESTINO, Marco; Viale Giovanni Pisano, 31, I-56123 Pisa (IT).
- (21) International Application Number: PCT/IB2002/005664 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 31 December 2002 (31.12.2002) (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (25) Filing Language: Italian
- (26) Publication Language: English
- (71) Applicants and  
(72) Inventors: SALSEDO, Fabio [IT/IT]; Via Umberto Primo, 100, I-04100 Latina (IT). DETTORI, Andrea [IT/IT]; Via Vecchia della Chiesa, 93h, I-54100 S. Maria a Colle (IT). BERGAMASCO, Massimo [IT/IT]; Via Don Minzoni, 144, I-56011 Castelmaggiore - Calci (IT). FRANCESCHINI, Marco [IT/IT]; Via Sarzanese, 247, S. Angelo in Campo, I-55100 Lucca (IT). FRISOLI, Antonio [IT/IT]; Via Emilia, 35/A, I-56100 Pisa (IT). ROCCHI, Fabrizio [IT/IT]; Via Roma, 114, I-00024 Castelmadrada (IT).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: EKOSKELETON INTERFACE APPARATUS



(57) Abstract: An exoskeleton interface apparatus comprises five rigid links (2-6) arranged in series, capable of rotating reciprocally at the respective ends for monitoring angular movements of the arm, of the forearm and the wrist of an user (60) and having at the tip an handgrip (30) for engaging with the user (60) by reflecting a force feedback. The rigid links (2-6) can rotate at their ends about rotational joints (11-14) having rotational axes (31-34) incident in the intersection point of the physiological axes of the shoulder. The rotational joints (11-14) are brought into rotation about the respective rotational axes (31-34) by means of respective motors (21-24), for example servo-motor such as torque motors. All the motors (21-24) are mounted on the fixed base link (2) in order to minimize the mass of the parts in movement and the inertia reflected on the user (60). A plurality is provided of idle pulleys (50) spatially arranged in space (figure 6) for orienting the tendons (41-44), which brake the free movement of the relative rotational joint, responsive to signals corresponding to constraints on the slave in case of Teleoperation or to constraints created by Virtual reality systems.

WO 2004/058458 A1